

शहर व औद्योगिक विकास महामंडळ (महाराष्ट्र) मर्यादित

'निर्मल', दुसरा मजला, नरीमन पाँईट, मुंबई - ४०० ०२१. मुख्य कार्यालय: दूष्यनी : (स्वागत कंक्ष) +९१-२२-६६५० ०९०० . सिडको' भवन, सीबीडी बेलापूर, नबी मुंबई-४०० ६१४. फैक्स : +९१-२२-२२०२ २५०९ दूष्वनी : +११-२२-६७९१ ८१०० CIDCO/ATPO(BP)/2010/7 8 2 6 -फेब्स : +११-२२-६७११ ८१६६ संदर्भ का रें, Ms. Shining Sun Construction Partner Shri, Nasir Jamal Shaikh & Others Two, 16/22, Bake House, MCC Lane, Fort, Mumbai. ASSESSEMENT ORDER NO.667/2010-11 REGISTER NO.03PAGE NO.667 SUB:-Payment of amended development charges for Residential Building on Plot No.104, Sector-14 at Taloja-Pachnand (12.5% scheme), Navi Mumbai. REF:- 1) Your architect's application dated 29/10/2010 & 25/11/2010 1) Your architect's application dated 29/10/2010 & 25/11/2010
2) Earlier C.C. granted by this office vide letter dtd. 23/09/2010
3) Delay condonation NOC issued by M(TS-II), vide letter dtd. 23/09/2010
4) Final Transfer Order Issued by M(TS-II), vide letter dtd. 28/11/2010
5) Fire NOC issued by Fire Officer, CIDCO vide letter dtd. 23/08/2010
6) Maveja NOC issued by M(TS) vide letter dtd. 17/09/2010
7) 50% IDC paid of Rs. 10, 50,000/- vide Challan No. 124800, dtd. 01/09/2010
ORDER OF ASSESSMENT OF DEVELOPMENT CHARGES.
(OFFICE ORDER NO. CIDCO.JADM/2449/DATED/18/11/92)
Name of Assessee

-M/s. Shining Sun Construction :-M/s. Shining Sun Construction Partner Shri, Nasir Jamal Shaikh & Others Two Location :-Plot No.104, Sector-14 at Taloja-Pachnand (12.5% scheme) Land use Plot area :- 2082.36 Sq. mtrs Permissible FSI AREA FOR ASSESSEMENT :-1.5 FOR COMMERCIAL i) Plot area :- 309.260 Sq.mtrs.. Built up area 463.890 Sq.mtrs. B) FOR RESIDENTIAL Plot area :- 1773.10 Sq.mtrs. Built up area DEVELOPMENT CHARGES 2655.375 Sq.mtrs FOR COMMERCIAL Plot area :- 309.260 Sq.mtrs. X Rs. 60/- = Rs.18555.60 Built up area ii) :- 463.890 Sq.mtrs. X Rs. 80/- = Rs.37111.20 B) FOR RESIDENTIAL TOTAL = Rs. 55666.80 i) Plot area :- 1773.10 Sq.mtrs. X Rs. 30/- = Rs. 53193.00 Built up area ii) :- 2655.375 Sq.mtrs X Rs. 40/- = <u>Rs.106215.00</u> TOTAL = Rs. 159408.00 Total Assessed development Charges:-7(A)+7(B)=Rs. 215074.80,Say Rs. 215075/Date of Assessment :- 26/11/2010 9) 10) Development charges paid of Rs. 2,15,200/- vide Challan No.124799, dtd.01/09/2010 :- 24/05/2007 to 23/05/2011 assessment order supersedes earlier assessement order No.452/2010-11 vide letter dtd.23/09/2010

> B. Patir Add. Town Planning Officer(BP) (Navi Mumbai & Khopta)



शहर व औद्योगिक विकास महामंडळ (महाराष्ट्र) मट

'निर्मल', दुसरा मजला, नरीमन पॉईट, मुंबई - ४०० ०२१.

दुरध्वनी : (स्वागत कहा) +९१-२२-६६५४ ७९००

: GR СФАТВФ(ВРУ2010/ 7 8 2 7

M/s. Shining Sun Construction

संदर्भ के. Partner Shri. Nasir Jamal Shaikh & Others Two. 16/22, Bake House, MCC Lane, Fort, Mumbai.

मुख्य कार्यालयः

'सिडको' भवन, सीबीडी बेलापूर, नवी मुंबई-४०० ६१४.

द्राध्वनी : +११-२२-६७११ ८१०० फेब्स : +११-२२-६७९१ ८१६६ :

^{दिनांक:} 3 0 NCV 2010

Sub:- Amended approved revised plan for Residential Building on Plot N.104, Sector-14 at Taloja-Pachnand (12.5% scheme), Navi Mumbai

REF:- 1) Your architect's application dated 29/10/2010 & 25/11/2010

2) Earlier C.C. granted by this office vide letter dtd.23/09/2010

2) Earlier C.C. granted by this office vide letter dtd.23/09/2010
3) Delay condonation NOC issued by M(TS-II), vide letter dtd.23/02/2010
4) Final Transfer Order issued by M(TS-II), vide letter dtd.28/11/2010
5) Fire NOC issued by Fire Officer, CIDCO vide letter dtd.23/08/2010
6) Maveja NOC issued by M(TS) vide letter dtd.17/09/2010
7) 50% IDC paid of Rs 10 50 000/s vide Challan No 124800 dtd.01/09/201

7) 50% IDC paid of Rs.10,50,000/- vide Challan No.124800, dtd.01/09/2010

Dear Sir.

Please refer to your application for amended development permission for Residential Building on Plot No.104, Sector-14 at Taloja-Pachnand (12.5% scheme), Navi Mumbai.

The amended development permission is hereby granted to construct Residential on the plot mentioned above.

The commencement certificate as required under section 45 of the Maharashtra Regional and Town Planning Act, 1966 is also enclosed herewith for the structures referred above.

The Developer / individual Plot Owner should obtain the proposed finished road edge level from the concerned Nodal Executive Engineer. The Developer/ Plot Owner to ensure that the finished plinth level of the proposed buildings / shops to be minimum 750 mm above the proposed finished road edge level. In case, the building is having stilt, the finished stilt level to be minimum 300 mm. above the road edge level.

The approval for plumbing services i.e. drainage and water supply shall be separately obtained by the applicant from the Executive Engineer, Kalamboli, CIDCO prior to the

You will ensure that for every 50 no. of flats, two wheeled bins of HDPE material and of capacity 240 liters each (1 no. for Dry and 1 No. for Wet Garbage) will be provided at site before

You will ensure that the building materials will not be stacked on the road during the construction period.

The Developers / Builders shall take all precautionary major for prevention of Malaria breeding during the construction period of the project. If required , you can approach Health Department CIDCO, for orientation program and pest control at project site to avoid epidemic.

Since, you have paid 50% IDC paid of Rs.10,50,000/- vide Challan No.124800, dtd.01/09/2010, you may approach to the Office of Executive Engineer (Kalamboli) to get the

This set of approved plans supercedes all the plans approved earlier. Thanking you,

> (R. B. Patil) Add. Town Planning Officer(BP) (Navi Mumbai & Khopta)

Yours faithful

	Pennission is hereby granted under said
	Planning Act. 1966 (Mahacashtra XXIVII) of 1966 to
	1013 Shiping S
*	Limited No 104 Road No 5
	Navi Mumbai, As per lie
	development work of the proposed Amended Rest Parisland (12.5-1) Rest. Bust = 2655. 375 mt 2 Total Bust = 3119.265 m² (Nos. of Residential Units 9.0.
	Comm. Bus 1033.375 m2 2 Total Bus
8	(Nos. of Residential Units 90 Nos. of Commercial units 20.) 1. This Certificate is total or
	Nos. of Commercial wait
	1. This Certificate is liable to be revolved by

- This Certificate is limble to be revoked by the Corporation if :-
 - The development work in respect of which permission is granted under this 1(n) certificate is not carried out or the use thereof is not in accordance with the
 - July of the conditions subject to which the same is granted or any of the restrictions imposed upon by the Corporation is contravened.
 - The Managing Director is satisfied that the same is obtained by the applicant through freed or Misrepresentation and the applicant and/or any person deriving title under him, in such an event shall be deemed to have curried out the development work in contravention of section-43 or 45 of the Maharashtra

. The applicant shall :

- Give a notice to the Corporation for completion of development work upto plinth 2(a) level, atleast 7 days before the commencement of the further work.
- Give written notice to the Corporation regarding completion of the work.
- Obtain Occupancy Certificate from the Corporation. 2(c)
- Permit authorised officers of the Corporation to enter the building or premises. 2(d) for which the permission has been granted, at any time for the purpose of ensuring the building control Regulations and conditions of this certificate.
- The structural design, building materials, installations, electrical installations etc. Shall he in accordance with the provision (except for provision in respect of floor area ratto) as prescribed in the National Building Code or and for GDCRs - 1975 in force.
- The Certificate shall remain valid for period of 1 year from the date of its issue, thereafter revalidation of the same shall be done in accordance with provision of Section-48 of MRTP Act- 1966 and as per regulation no.16.1(2) of the GDCRs - 1975.

- 5. The conditions of this certificate shall be binding not only on the applicant but also on its successors and for every person deriving title through or under him.
- 6. A certified copy of the approved plan shall be exhibited on site.
- The amount of Rs. 10.500 deposited with CIDCO as security deposit shall be of any of the conditions attached to the permission covered by the Commencement Corporation.

 Such forfeiture shall be without prejudice to any other remedy or right of the conditions.
- Every Building shall be provided with under ground and over head water tank. The capacity of the tanks shall be as per norms fixed by CIDCO. In case of high rise requirements of CIDCO. The applicant shall seek approval of the EE(Water Supply) of approval of the Fire Officer of CIDCO in respect of capacity of domestic water tanks. The applicant shall seek fighting purpose.
- You shall approach Executive Engineer, M.S.E.B. for the power requirements, location
 As not Court of the court of the court of the power requirements, location
- As per Gevt. of Maharashtra memorandum vide No.TBP/4393/1504/C4-287/94, UD-11/RDP, Dated 19th July, 1994 for all buildings following additional conditions shall
 - i] As soon as the development permission for new construction or re-development is obtained by the Owners/Developer, he shall install a 'Display Board' on the conspicuous place on site indicating following details:
 - a) Name and address of the owner/developer, Architect and Contractor.
 - b) Survey Number/City survey Number. Plot, Number/Sector & Nixle of Land under reference alongwith description of its boundaries.
 - Order Number and date of grant of development permission or re-development
 Number of Paristration of Authority or any other authority.
 - d) Number of Residential flats/Commercial Units with areas.
 - e) Address where copies of detailed approved plans shall be available for inspection.
 - ii) A notice in the form of an advertisement, giving all the detailed mentioned in (i) above, shall be published in two widely circulated newspapers one of which should be in regional language.

As per the notification dtd. 14th September 1999 and amendment on 27th August 2003, issued by Ministry of Environment & Forest (MOEF), Govt. of India and as per Circular issued by Urban Development Deptt., Govt. of Maharashtra, vide No. FAR/102004/160/P.No.27/UD-20, dtd. 27/02/2004, for all Buildings following additional

The Owners Developer shall use Fly Ash bricks or blocks or tiles or clay fly ash bricks or cement fly ash bricks or blocks or similar products or a combination of aggregate of them to the extent of 100% (by volume) of the total bricks, blocks & tiles as the case may be in their construction activity.

- As directed by the Urban Development Deptt. Government of Maharashtra, under Section-154 of MR&TP Act-1966 and vide Provision No. TPB 432001/2133/CR-230/01/UD-11, dated 10/03/2005, for all buildings greater than 300.00 Sq.m. following additional condition of Rain Water Harvesting shall apply.
 - All the layout open spaces / amenities spaces of Housing Society and new construction / reconstruction / additions on plots having area not less than 300.00 Sq.m., shall have one or more Rain Water Harvesting structures having minimum total capacity as detailed in schedule (enclosed.)

Provided that the authority may approve the Rain Water Harvesting Structures of specifications different from those in Schedule, subject to the minimum capacity of Rain Water Harvesting being ensured in each case.

- The owner / society of every building mentioned in the (a) above shall ensure that the Rain Water Harvesting structure is maintained in good repair for storage of water for non potable purposes or recharge of groundwater at all times.
- The Authority may impose a levy, of not exceeding Rs. 100/- per annum for every 100 Sq.m. of built up area for the failure of the owner of any building mentioned in the (a) above to provide or to maintain Rain Water Harvesting structures as

ADDL TOWN PLANNING OFFICER Navi Mumbai & Khopta

C.C.TO: ARCHITECT

m/s. Triarch

C.C. TO: Separately to:

M(TS)

2. CUC

3. EE(KHR/PNL/KLM/DRON)

EE(WS)

Rain Water Harvesting in a building site includes storage or recharging into ground of rain water falling on the terrace or on any paved or unpaved surface

- The following systems may be adopted for harvesting the rain water drawn from terrace and the paved surface.
 - Open well of a minimum of 1.00 mt. dia and 6 mt. in depth into which rain water may be channeled and allowed after fluration for removing silt and floating material. The well shall be provided with ventilating covers. The water from the open well may be used for non potable domestic purposes such as washing, flushing and for (ii)
 - Rain water harvesting for recharge of ground water may be done through a bore well around which a pit of one metre width may be excavated upto a depth of at least 3.00 mt. and refilled with stone aggregate and sand. The filtered rain water may be channeled to the refilled pit for recharging the botewell. (iii)
 - An impervious surface /underground storage tank of required capacity may be constructed in the setback or other open space. and the rain water may be channeled to the storage tank. The storage tank shall always be provided with ventilating covers and shall have draw-off taps suitably placed so that the rain water may be drawn off for domestic, washing gardening and such other purposes. The storage tanks shall be provided with an overflow.
 - The surplus rain water after storage may be recharged into ground through percolation pits or trenches or combination of pits and trenches. Depending on the geomorphological and topographical condition, the pits may be of the size of 1.20 mt. width X 1.20 mt. length X 2.00 mt. to 2.50 mt. depth. The trenches can be or 0.60 mt. width X 2.00 to 6.00 mt. length X 1.50. to 2.00 mt. depth. Terrace water shall be channeled to pits or trenches. Such pits or trenches shall be back filled with filter media comprising the
 - a) 40 mm stone aggregate as bottom layer upto 50% of the depth;
 - b) 20 mm stone aggregate as lower middle layer upto 20% of the
 - c) Coarse sand as upper middle layer upto 20% of the depth; d) A thin layer of line sand as top layer;

ROTA/H-984(B)(400-03-2005)-3

c) Top 10% of the pits/trenches will be empty and a splash is to be provided in this portion in such a way that roof top water falls on the splash pad.

Brick masonry wall is to be constructed on the exposed surface

of pits/trenches and the cement mortar plastered.

The depth of wall below ground shall be such that the wall prevents lose soil entering into pits/trenches. The projection of the wall above ground shall atleast be 15 cms.

- Perforated concrete slabs shall be provided on the pits/trenches.
- If the open space surrounding the building is not paved, the top layer upto a sufficient depth shall be removed and refilled with course sand to allow percolation of rain water into ground.
- The terrace shall be connected to the open well/borewell/storage tank/recharge pit/trench by means of HDPE/PVC pipes through filter media. A valve system shall be provided to enable the first washings from roof or terrace catchment, as they would contain undesirable dirt. The mouths of all pipes and opening shall be covered with mosquito (insect). proof wire net. For the efficient discharge of rein water, there shall be at least two rain water pipes of 100 mm dia mtr. for a roof area of 100

Rain water harvesting structures shall be sited as not to endanger the stability of building or earthwork. The structures shall be designed such that no dampness is caused in any part of the walls or foundation of the

building or those of an adjacent building. The water so collected/recharged shall as far as possible be used for non-drinking and non-cooking purpose.

Provided that when the rain water in exceptional circumstances will be utilized for drinking and/or cooking purpose, it shall be ensured that proper filter arrangement and the separate outlet for by passing the first rain-water has been provided.

Provided further that it will be ensured that for such use, proper disinfectants and the water purification arrangements have been made.