

# CITY AND INDUSTRIAL DEVELOPMENT CORPORATION OF MAHARASHTRA LIMITED

**REGD. OFFICE:**

"NIRMAL", 2nd Floor, Nariman Point,  
 Mumbai - 400 021.  
 PHONE : (Reception) +91-22-6650 0900 / 6650 0928  
 FAX : +91-22-2202 2509 / 6650 0933

**HEAD OFFICE:**

CIDCO Bhavan, CBD Belapur,  
 Navi Mumbai - 400 614.  
 PHONE : +91-22-6791 8100  
 FAX : +91-22-6791 8166

Date: **26 JUN 2012**

Ref. No. CIDCO/BP-3024/ATPO(NM & K)/2012/

**389---**

Unique Code No.	2	0	1	2	0	3	0	2	1	0	2	1	5	0	3	0	1
-----------------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

To,  
 M/s. Adhiraj Constructions Pvt. Ltd.,  
 303, Sharda Chambers,  
 15, New Marine Lines, Mumbai.

Sub:- Amended approval to revised plans for Residential-Cum-Commercial Building on Plot No.32, Sector-5, Kharghar, Navi Mumbai.

REF:- 1) Your architect's application dated 21/02/2012

2) Your letter dtd.02/12/2011 & 19/06/2012

3) Earlier C.C. granted by this office vide letter No.CIDCO/ATPO(BP)/1726, dtd.11/11/2010

4) PSIDC NOC issued by EE(Elect), vide letter No.CIDCO/EE(Elect)/09/897, dtd.09/09/2009

5) Fire NOC issued by Fire Officer, vide letter No.CIDCO/Fire/KIm/2477/2012, dtd.23/02/2012

6) MSEDCL NOC issued by EE, Panvel (U) Div. vide letter No.CIDCO/EE Panvel(U) division/006324, dtd.11/11/2009

7) Environmental clearance issued by Addl. Dir(IA), MOEF vide letter No.21-878/2007-IA,III, dtd.03/04/2008

8) Modified Agreement dtd.28/01/2008 for Addl. FSI 0.50

9) NOC for Extension of time limit issued by AEO(Khr) vide letter No.CIDCO/Estate-III)/2012/WS-1469, dtd.18/06/2012

10) NOC from Airport Authority of India vide letter No. BT-1/NOCC/CS/MUM/10/NM/1002, dtd.23/11/2011

Dear Sir,

Please refer to your application for amended development permission for Residential-Cum-Commercial Building on Plot No.32, Sector-5, Kharghar, Navi Mumbai.

The amended development permission is hereby granted to construct Residential-Cum-Commercial Building on the plot mentioned above.

The commencement certificate as required under section 45 of the Maharashtra Regional and Town Planning Act, 1966 is also enclosed herewith for the structures referred above.

The Developer / individual Plot Owner should obtain the proposed finished road edge level from the concerned Nodal Executive Engineer. The Developer/ Plot Owner to ensure that the finished plinth level of the proposed buildings / shops to be minimum 750 mm above the proposed finished road edge level. In case, the building is having stilt, the finished stilt level to be minimum 300 mm. above the road edge level.

The approval for plumbing services i.e. drainage and water supply shall be separately obtained by the applicant from the Executive Engineer, Kharghar, CIDCO prior to the commencement of the construction Work.

The Developers / Builders shall take all precautionary measures for prevention of Malaria breeding during the construction period of the project. If required, you can approach Health Department CIDCO, for orientation program and pest control at project site to avoid epidemic.

You will ensure that the building materials will not be stacked on the road during the construction period.

You will ensure that for every 50 no. of flats, two wheeled bins of HDPE material and of capacity 240 liters each (1 no. for Dry and 1 No. for Wet Garbage) will be provided at site before seeking occupancy certificate.

This set of approved plans supercedes all the plans approved earlier.

Thanking you,

Yours faithfully,

( R. B. Patil )

Addl. Town Planning Officer(BP)  
 (Navi Mumbai & Khopta)

CITY & INDUSTRIAL DEVELOPMENT CORPORATION OF MAHARASHTRA LTD.AMENDED COMMENCEMENT CERTIFICATE


Permission is hereby granted under section – 45 of the Maharashtra Regional and Town Planning Act. 1966 (Maharashtra XXIV) of 1966 to **M/s. Adhiraj Constructions Pvt. Ltd.** **Plot No. 32, Sector- 05, Node– Kharghar** of Navi Mumbai. As per the approved plans and subject to the following conditions for the development work of the proposed **Residential-Cum-Commercial Buildings, [Residential Buildings - Cypress (G+21 Floors), Aqua (G+22 Floors), Zenia (G+19 Floors), Common Toilet, Badminton Court and Commercial Building 'P' (G+3 Floors)]**  
**Total Residential BUA = 21778.30 SQM and Total Commercial BUA = 4896.12 SQM,**  
**Total Net Built Up Area = 26674.42 SQM** (Nos. of Residential Units = 307, Nos. of Commercial units = 08)

1. **This Certificate is liable to be revoked by the Corporation if :**
  - 1(a) The development work in respect of which permission is granted under this certificate is not out or the use thereof is not in accordance with the Sanctioned plans.
  - 1(b) Any of the conditions subject to which the same is granted or any of the restrictions imposed upon by the corporation is contravened.
  - 1(c) The Managing Director is satisfied that the same is obtained by the applicant through fraud or Misrepresentation and the applicant and/or any person deriving title under him, is such as event shall be deemed to have carried out the development work in contravention of section 13 or 45 of the Maharashtra Regional and Town Planning Act- 1966.
  
2. **The applicant shall :**
  - 2(a) Give a notice to the Corporation for completion of development work upto plinth level, atleast 7 days before the commencement of the further work.
  - 2(b) Give written notice to the corporation regarding completion of the work.
  - 2(c) Obtain Occupancy from the Corporation.
  - 2(d) Permit authorized officers of the Corporation to enter the building or premises for which the permission has been granted at any time for the purpose of ensuring the building control Regulations and conditions of the certificate.
  
3. The structural design, building materials, installations, electrical installations etc. shall be in accordance with the provision (except for provision in respect of floor area ratio) as prescribed in the National Building Code or and/or GDCRs- 1975 in force.





4. The Certificate shall remain valid for period of 1 year from the date of its issue, thereafter revalidation of the same shall be done in accordance with provision of Section – 48 of MRTP Act- 1966 and as per regulation no 16.1 (2) of the GDCRs – 1975.
5. The conditions of this certificate shall be binding not only on the applicant but also on its successors and/or every person deriving title through or under him.
6. A certificate copy of the approved plan shall be exhibited on site.
7. The amount of **Rs 18,25,000/-** deposited with CIDCO as security deposit shall be forfeited either in whole or in part at the absolute discretion of the Corporation for breach of any of conditions attached to the permission covered by the Commencement Certificate. Such forfeiture shall be without prejudice to any other remedy or right of Corporation.
8. "Every Building shall be provided with under ground and over head water tank. The capacity of the tanks shall be as per norms fixed by CIDCO. In case of high rise buildings under ground and over head water tank shall be provided as per the fire fighting requirements of CIDCO. The applicant shall seek approval of the EE (Water Supply) of CIDCO in respect of capacity of domestic water tanks. The applicant shall seek approval of the Fire Officer of CIDCO in respect of capacity of water tanks for the fighting purpose".
9. You shall approach Executive Engineer, M.S.E.B. for the power requirements, location, of transformer, if any, etc.
10. As per Govt. of Maharashtra memorandum vide No. TBP/4393/1504/C4-287/94, UD-11/RDP, Dated 19<sup>th</sup> July, 1994 for all buildings following additional conditions shall apply.
  - i) As soon as the development permission for new construction or re-development is obtained by the Owners/Developer, he shall install a 'Display Board' on the conspicuous place on site indicating following details :-
    - a) Name and address of the owner/developer, Architect and Contractor.
    - b) Survey Number/City survey Number, Plot Number/Sector & Node of Land under reference alongwith description of its boundaries.
    - c) Order Number and date of grant of development permissions or re-development permission issued by the Planning Authority or any other authority.
    - d) Number of Residential flats/Commercial Units with areas.
    - e) Address where copies of detailed approved plans shall be available for inspection.
  - ii) A notice in the form of an advertisement, giving all the detailed mentioned in (i) above, shall be published in two widely circulated newspapers one of which should be in regional language.



11. As per the notification dtd. 14<sup>th</sup> September 1999 and amendment on 27th August 2003, issued by Ministry of Environment & Forest (MOEF), Govt. of India and as per Circular issued by Urban Development Deptt., Govt. of Maharashtra, vide No. FAR/102004/160/P.No. 27/UD-20, dtd. 27/02/2004, for all Buildings following additional conditions shall apply.  
The Owners/Developer shall use Fly Ash bricks or tiles of clay fly ash bricks or cement fly ash bricks or blocks or similar products or a combination of aggregate of them to the extent of 100 % (by volume) of the total bricks, blocks & tiles as the case may be in their construction activity.
12. As directed by the Urban Development Deptt. Government of Maharashtra under Section - 154 of MR & TP Act- 1966 and vide Provision No. TPB 432001/2133/CR-230/01/UD-11, dated 10/03/2005, for all buildings greater than 300.00 Sq. m. following additional condition of Rain Water Harvesting shall apply.
- a) All the layout open spaces/amenities spaces of Housing Society and new construction /reconstruction / additions on plots having area not less than 300.00 Sq.m. shall have one or more Rain Water Harvesting structures having minimum total capacity as detailed in schedule (enclosed).  
Provided that the authority may approve the Rain water Harvesting Structures of specifications different from those in Schedule, subject to the minimum capacity of Rain Water Harvesting being ensured in each case.
- b) The owner/society of every building mentioned in the (a) above shall ensure that the Rain Water Harvesting structure is maintained in good repair for storage of water for non potable purposes or recharge of groundwater at all times.
- c) The Authority may imposed a levy of not exceeding Rs. 100/- per annum for every 100 Sq. m. of built up area for the failure of the owner of any building mentioned in the (a) above to provide or to maintain Rain Water Harvesting structures as required under these byelaws.

  
ADDL. TOWN PLANNING OFFICER  
Navi Mumbai & Khopta

C.C. TO : ARCHITECT  
M/s. Deepak Mehta

C.C. TO : Separately to :

1. M(TS)
2. CUC
3. EE(KHR/PNL/KLM/DRON)
4. EE(WS)



SCHEDULE  
RAIN WATER HARVESTING

Rain Water Harvesting in a building site includes storage or recharging into ground of rain water falling on the terrace or on any paved or unpaved surface within the building site.

1. The following systems may be adopted for harvesting the rain water drawn from terrace and the paved surface.
  - (i) **Open well** of a minimum of 1.00 mt. dia and 6 mt. in depth into which rain water may be channeled and allowed after filtration for removing silt and floating material. The well shall be provided with ventilating covers. The water from the open well may be used for non potable domestic purposes such as washing, flushing and for watering the garden etc.
  - (ii) Rain water harvesting for recharge of ground water may be done through a **bore well** around which a pit of one metre width may be excavated upto a depth of at least 3.00 mt. and refilled with stone aggregate and sand. The filtered rain water may be channeled to the refilled pit for recharging the borewell.
  - (iii) An impervious surface/ underground storage tank of required capacity may be constructed in the setback or other open space and the rain water may be channeled to the storage tank. The storage tank shall always be provided with ventilating covers and shall have draw-off taps suitably placed so that the rain water may be drawn off for domestic, washing, gardening and such other purposes. The storage tanks shall be provided with an overflow.
  - (iv) The surplus rain water after storage may be recharged into ground through percolation pits or trenches or combination of pits and trenches. Depending on the geomorphological and topographical condition, the pits may be of the size of 1.20 mt. width X 1.20 mt. length X 2.00 mt. to 2.50. mt. depth. The trenches can be of 0.60 mt. width X 2.00 to 6.00 mt. length X 1.50 to 2.00 mt. depth. Terrace water shall be channeled to pits or trenches. Such pits or trenches shall be back filled with filter media comprising the following materials.
    - a) 40 mm stone aggregate as bottom layer upto 50% of the depth;
    - b) 20 mm stone aggregate as lower middle layer upto 20% of the depth;
    - c) Coarse sand as upper middle payer upto 20% of the depth;
    - d) A thin layer of fine sand as top layer;
    - e) Top 10% of the pits/ trenches will be empty and a splash is to be provided in this portion in such a way that roof top water falls on the splash pad.

JBT

f) Brick masonry wall is to be constructed on the exposed surface of pits/ trenches and the cement mortar plastered.

The depth of wall below ground shall be such that the wall prevents loose soil entering into pits/ trenches. The projection of the wall above ground shall atleast be 15 cms.

g) Perforated concrete slabs shall be provided on the pits/trenches.

(v) If the open space surrounding the building is not paved, the top layer upto a sufficient depth shall be removed and refilled with coarse sand to allow percolation of rain water into ground.

2. The terrace shall be connected to the open well/borewell/storage tank/recharge pit/trench by means of HDPE/PVC pipes through filter media. A valve system shall be provided to enable the first washings from roof or terrace catchment, as they would contain undesirable dirt. The mouths of all pipes and opening shall be covered with mosquito (insect) proof wire net. For the efficient discharge of rain water, there shall be at least two rain water pipes of 100 mm dia mtr, for a roof area of 100 Sq. mt.

3. Rain water harvesting structures shall be sited as not to endanger the stability of building or earthwork. The structures shall be designed such that no dampness is caused in any part of the walls or foundation of the building or those of an adjacent building

4. The water so collected/recharged shall as far as possible be used for non-drinking and non-cooking purpose.

Provided that when the rain water in exceptional circumstances will be utilized for drinking and/or cooking purpose, it shall be ensured that proper filter arrangement and the separate outlet for by passing the first rain-water has been provided.

Provided further that it will be ensured that for such use, proper disinfectants and the water purification arrangements have been made.

